



DEVELOPMENT SERVICES DEPARTMENT
14700 RAVINIA AVENUE
ORLAND PARK, ILLINOIS 60462
708-403-5300 FAX 708-403-6215
developmentservices@orlandpark.org
www.orlandpark.org

Permit # _____

Flatwork Requirements

DRIVEWAYS

- Maximum Driveway Width from building line to curb:
 - 20' - 1 Car Garage
 - 26' - 2 Car Garage
 - 36' - 3 Car Garage
- ASPHALT
 - Minimum 2" stone base. Minimum 2-1/2" thickness of asphalt.
- CONCRETE
 - Minimum 2" stone base. 5" concrete thickness formed with 2"x 6" forms. 6 bag mix reinforced with 6x6x10 wire or fiber mesh.

CONCRETE

- *Patios & Private Sidewalks:* Minimum 2" stone base, 4" concrete thickness.
- *Public Sidewalks:* Minimum 2" stone base. 5" concrete thickness formed with 2" x 6" forms. 6 bag mix reinforced with 6 x 6 x 10 wire or fiber mesh thru driveway.
- *Garage Slab:* Minimum 2" stone base. 5" concrete thickness reinforced with 6x6x10 gauge wire or fiber mesh. Minimum 6 bag mix.

PAVER BRICKS

- *Patios, Walks, Driveways:* Minimum 4" of compacted stone base.

See additional 'Inspections Required' Handout with permit. Inspections may be submitted:
In person at Development Services Department, by fax to (708) 403-6215,
on website at www.orlandpark.org, or email to inspectionrequest@orlandpark.org.
Inspection requests are NOT taken over the phone.

PRINT NAME _____

DATE _____

SIGNATURE _____